

Package: pargasite (via r-universe)

August 22, 2024

Title Pollution-Associated Risk Geospatial Analysis Site

Version 2.1.0

Description Offers tools to estimate and visualize levels of major pollutants (CO, NO₂, SO₂, Ozone, PM_{2.5} and PM₁₀) across the conterminous United States for user-defined time ranges. Provides functions to retrieve pollutant data from the U.S. Environmental Protection Agency's 'Air Quality System' (AQS) API service
<https://aqs.epa.gov/aqsweb/documents/data_api.html> for interactive visualization through a 'shiny' application, allowing users to explore pollutant levels for a given location over time relative to the National Ambient Air Quality Standards (NAAQS).

License BSD_3_clause + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.1

Imports cli, gstat, leaflet, leafsync, methods, raqs, rlang, sf (>= 1.0-15), shiny, shinycssloaders, stars (>= 0.6-5), stats, utils

Depends R (>= 4.1.0)

LazyData true

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Jaehyun Joo [aut, cre], Rebecca Greenblatt [aut], Avantika Diwadkar [aut], Nisha Narayanan [aut], Blanca Himes [aut]

Maintainer Jaehyun Joo <jaehyunjoo@outlook.com>

Date/Publication 2024-04-23 11:20:02 UTC

Repository <https://jaehyunjoo.r-universe.dev>

RemoteUrl <https://github.com/cran/pargasite>

RemoteRef HEAD

RemoteSha f5f65abed47dba8392a3200942f7931ab44e3a0f

Contents

pargasite-package	2
create_pargasite_data	2
create_raster	5
list_pollutant_standards	6
ozone20km	7
run_pargasite	8

Index	9
--------------	----------

pargasite-package	<i>pargasite: Pollution-Associated Risk Geospatial Analysis Site</i>
-------------------	--

Description

Offers tools to estimate and visualize levels of major pollutants (CO, NO₂, SO₂, Ozone, PM_{2.5} and PM₁₀) across the conterminous United States for user-defined time ranges. Provides functions to retrieve pollutant data from the U.S. Environmental Protection Agency's 'Air Quality System' (AQS) API service https://aq5.epa.gov/aq5web/documents/data_api.html for interactive visualization through a 'shiny' application, allowing users to explore pollutant levels for a given location over time relative to the National Ambient Air Quality Standards (NAAQS).

Author(s)

Maintainer: Jaehyun Joo <jaehyunjoo@outlook.com>

Authors:

- Rebecca Greenblatt
- Avantika Diwadkar
- Nisha Narayanan
- Blanca Himes

create_pargasite_data	<i>Create a data cube for air pollutant levels covering the conterminous United States</i>
-----------------------	--

Description

A function to create a raster-based pollutant concentration input for pargasite's shiny application. It downloads pollutant data via the Environmental Protection Agency's (EPA) Air Quality System (AQS) API service, filters the data by exceptional event (e.g., wildfire) status, and performs the inverse distance weighted (IDW) interpolation to estimate pollutant concentrations covering the conterminous United States (CONUS) at user-defined time ranges.

Usage

```

create_pargasite_data(
  pollutant = c("CO", "SO2", "NO2", "Ozone", "PM2.5", "PM10"),
  data_field = c("NAAQS_statistic", "arithmetic_mean"),
  event_filter = c("Events Included", "Events Excluded", "Concurred Events Excluded"),
  year,
  by_month = FALSE,
  cell_size = 10000,
  nmax = Inf,
  aqs_email = get_aqs_email(),
  aqs_key = get_aqs_key(),
  download_chunk_size = c("2-week", "month")
)

```

Arguments

pollutant	A string specifying an air pollutant to create a raster data cube. Must be one of CO2, SO2, NO2, Ozone, PM2.5 and PM10.
data_field	A vector of strings specifying whether which data fields are used to summarize the data. Must be either 'NAAQS_statistic', 'arithmetic_mean', or both. 'NAAQS_statistic' try to chooses an appropriate field based on National Ambient Air Quality Standards (NAAQS) in the AQS yearly data (e.g, for CO 1-hour average, 'second_max_value' would be chosen). 'arithmetic_mean' represents the measure of central tendency in the yearly data. Ignored when by_month = TRUE.
event_filter	A vector of strings indicating whether data measured during exceptional events are included in the summary. 'Events Included' means that events occurred and the data from theme is included in the summary. 'Events Excluded' means that events occurred but data from them is excluded from the summary. 'Concurred Events Excluded' means that events occurred but only EPA concurred exclusions are removed from the summary. If multiple values are specified, pollutant levels for each filter are stored in event dimension in the resulting output.
year	A vector of 4-digit numeric values specifying years to retrieve pollutant levels.
by_month	A logical value indicating whether data summarized at monthly level instead of yearly level.
cell_size	A numeric value specifying a cell size of grid cells in meters.
nmax	An integer value specifying the number of nearest observations that should be used for spatial interpolation.
aqs_email	A string specifying the registered email for AQS API service.
aqs_key	A string specifying the registered key for AQS API service.
download_chunk_size	A string specifying a chunk size for AQS API daily data download to prevent an unexpected server timeout error. Ignored when by_month = FALSE.

Details

By default, it returns yearly-summarized concentrations using AQS's annual data but can also provide monthly-summarized concentrations by aggregating AQS's daily data. Note that the function chooses an appropriate data field for each pollutant to check the air quality status based on the National Ambient Air Quality Standard (NAAQS) for yearly-summarized outputs as follows

- CO 1-hour: `second_max_value` field
- CO 8-hour: `second_max_nonoverlap` field
- SO2 1-hour: `ninety_ninth_percentile` field
- NO2 1-hour: `nineth_eighth_percentile` field
- NO2 Annual: `arithmetic_mean` field
- Ozone 8-hour: `fourth_max_value` field
- PM10 24-hour: `primary_exceedance_count` field
- PM25 24-hour: `ninety_eighth_percentile` field
- PM25 Annual: `arithmetic_mean` field

For monthly-summarized outputs, it uses the `arithmetic_mean` field of daily data. Please check AQS API `metaData/fieldsByService` (see [raqs::metadata_fieldsbyservice](#)) and [AQS data dictionary](#) for the details of field descriptions.

For spatial interpolation, the AQS data is projected to EPSG:6350 (NAD83 CONUS Albers), and thus, `cell_size` value is represented in meters (5,000 creates 5km x 5km grid). The smaller `cell_size`, the more processing time is required.

Value

A stars object containing the interpolated pollutant levels over CONUS.

Examples

```
## Not run:

## Set your AQS API key first using [raqs::set_aqs_user] to run the example.

## SO2 and CO concentrations through 2020 to 2022
so2 <- create_pargasite_data("SO2", "Events Included", year = 2020:2022)
co <- create_pargasite_data("CO", "Events Included", year = 2020:2022)

## Combine them; can combine other pollutant grids in the same way
pargasite_input <- c(so2, co)

## End(Not run)
```

create_raster	<i>Raster creation function</i>
---------------	---------------------------------

Description

This function is used internally by [create_pargasite_data](#), allowing users to specify a longitude/latitude bounding box. It is exported for package development, not for direct user calls.

Usage

```
create_raster(
  parameter_code,
  pollutant_standard = NULL,
  data_field = c("NAAQS_statistic", "arithmetic_mean"),
  event_filter = c("Events Included", "Events Excluded", "Concurred Events Excluded"),
  year,
  by_month = FALSE,
  minlat = 24,
  maxlat = 50,
  minlon = -124,
  maxlon = -66,
  crs = 6350,
  cell_size = 10000,
  aqs_email = get_aqs_email(),
  aqs_key = get_aqs_key(),
  nmax = Inf,
  download_chunk_size = c("2-week", "month")
)
```

Arguments

parameter_code	A numeric value specifying a AQS parameter code.
pollutant_standard	A vector of strings specifying unique pollutant standards in AQS (e.g., PM25 Annual 2012).
data_field	A vector of strings specifying whether which data fields are used to summarize the data. Must be either 'NAAQS_statistic', 'arithmetic_mean', or both. 'NAAQS_statistic' try to chooses an appropriate field based on National Ambient Air Quality Standards (NAAQS) in the AQS yearly data (e.g, for CO 1-hour average, 'second_max_value' would be chosen). 'arithmetic_mean' represents the measure of central tendency in the yearly data. Ignored when by_month = TRUE.
event_filter	A vector of strings indicating whether data measured during exceptional events are included in the summary. 'Events Included' means that events occurred and the data from theme is included in the summary. 'Events Excluded' means that events occurred but data from them is excluded from the summary. 'Concurred

	Events Excluded' means that events occurred but only EPA concurred exclusions are removed from the summary. If multiple values are specified, pollutant levels for each filter are stored in event dimension in the resulting output.
year	A vector of 4-digit numeric values specifying years to retrieve pollutant levels.
by_month	A logical value indicating whether data summarized at monthly level instead of yearly level.
minlat, maxlat, minlon, maxlon	A numeric value specifying a bounding box defined by two latitudes and two longitudes.
crs	A target coordinate reference system.
cell_size	A numeric value specifying a cell size of grid cells in meters.
aqs_email	A string specifying the registered email for AQS API service.
aqs_key	A string specifying the registered key for AQS API service.
nmax	An integer value specifying the number of nearest observations that should be used for spatial interpolation.
download_chunk_size	A string specifying a chunk size for AQS API daily data download to prevent an unexpected server timeout error. Ignored when by_month = FALSE.

Value

A stars object containing the interpolated pollutant levels covering the user-specified bounding box.

Examples

```
## Not run:

## Set your AQS API key first using [raqs::set_aqs_user] to run the example.

## SO2 through 2021 to 2022
so2 <- create_raster(42401, event_filter = "Events Included",
                    year = 2021:2022)

## End(Not run)
```

list_pollutant_standards

Look up National Ambient Air Quality Standards (NAAQS)

Description

A function to show pollutant standard information on criteria air pollutants.

Usage

```
list_pollutant_standards(parameter_code = NULL, detail = FALSE)
```

Arguments

`parameter_code` An AQS parameter code to retrieve specific standard information. If NULL (default), display all pollutant standards.

`detail` A logical value indicating whether detailed information is retrieved.

Value

A data.frame containing the pollutant standard information

References

Data source: https://aqs.epa.gov/aqsweb/documents/codetables/pollutant_standards.html

Examples

```
list_pollutant_standards()
```

ozone20km

Ozone concentration data

Description

A stars object containing ozone concentrations covering the conterminous United States for years 2021-2022 on a 20km x 20km grid.

Usage

```
ozone20km
```

Format

A stars object with 4 dimensions and 1 attribute

x, y dimension; raster coordinates

event dimension; exceptional event filter

year dimension; years of data available

ozone_8_hour_2015 attribute; ozone levels based on Ozone 8-hour 2015 standard

`run_pargasite`*Run pargasite application*

Description

Launch a Shiny application to visualize pollutant levels of the conterminous US. The system's default web browser will be launched automatically after the app is started.

Usage

```
run_pargasite(x)
```

Arguments

`x` A stars object returned by [create_pargasite_data](#).

Value

This function normally does not return; interrupt R to stop the application (usually by pressing Ctrl + C or ESC).

Examples

```
if (interactive()) {  
  run_pargasite(ozone20km)  
}
```


Index

* datasets

- ozone20km, [7](#)
- create_pargasite_data, [2](#), [5](#), [8](#)
- create_raster, [5](#)
- list_pollutant_standards, [6](#)
- ozone20km, [7](#)
- pargasite (pargasite-package), [2](#)
- pargasite-package, [2](#)
- raqs::metadata_fieldsbyservice, [4](#)
- run_pargasite, [8](#)